DUCHESNE COUNTY MONUMENT SURVEY RECORD

T1S R3W

SEC 16 | SEC 15

SEC 21 SEC 22

U.S.B.&M.



N 89°59'23" W

2642.28

S 66'11'09" W 131.36'
S 66'11'09" W PIPE
TO FACE OFNER
FENCE CORNER

NOTE:

THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. OBSERVATIONS AT A CONTROL POINT (SECTION CORNER) LOCATED AT LAT.

40°21'33.88695"N AND LONG. 110°13'06.20894"W USING THE UTAH STATE G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER

NAIL AND WASHER ON SOUTH SIDE OF POWER POLE

NAIL AND WASHER ON SOUTH SIDE OF POWER POLE

NAIL AND WASHER ON SOUTH SIDE OF POWER POLE

OF FACE OF PIPE FENCE CORNER

CENTER BOLT OF FIRE HYDRANT

FOUND A REBAR WITH A 2½"


NAIL AND WASHER
ON EAST SIDE OF
FENCE CORNER


00.35,05"

163.21"

S

FOUND A REBAR WITH A 2½" ALUMINUM DUCHESNE COUNTY MONUMENT AT 1/4 CORNER





 $\begin{array}{ccc}
SCALE: & I = 30 \\
0' & & 30'
\end{array}$

DESCRIPTION OF CORNER EVIDENCE FOUND

FOUND AN ALUMINUM DUCHESNE COUNTY PIPE MONUMENT AT THE POSITION OF THE SECTION CORNER

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE CORNER

FACE OF PIPE OF FENCE CORNER

RESET MONUMENT AFTER ROAD CONSTRUCTION



MARKINGS ON MONUMENT

STATE PLANE COORDINATE DATA

(U.S. SURVEY FEET)

NAD83 UTAH CENTRAL ZONE
N: 7312764.259
E: 1997414.568

E: 1997414.568 NAVD88 EL: 6309.91'

LATITUDE: 40°23′18.24584″ N **LONGITUDE:** 110°13′06.04239″ W

ELLIPSOID HEIGHT: 6256.72' (GEOID 03 CONUS)

PUBLIC LAND SURVEY SYSTEM GCDB ID NO. UT300010S0030W0_400400



PHOTO OF MONUMENT FACING NORTH

CERTIFICATION

I <u>Jerry D. Allred</u>, Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

FACE OF PIPE FENCE CORNER

Jerry D. Allred, Professional Land Surveyor Certificate No. 148951 Duchesne County Surveyor

